

MIRAI MR10-01 Leg1 Conductivity-Temperature-Depth Profiler (CTD)

Last Modified: 2017-06-22

[ReadMe](#) [Observation Data](#) [Data Format](#)

Cruise ID: [MR10-01 Leg1](#)

Conductivity-Temperature-Depth Profiler (CTD): Processed (DMO)-QCed

Data Policy: [JAMSTEC](#)

Observation Items: Pressure, Temperature, Salinity, Dissolved oxygen

Science Keywords:

OCEANS > OCEAN CHEMISTRY > OXYGEN
OCEANS > OCEAN TEMPERATURE > WATER TEMPERATURE
OCEANS > SALINITY/DENSITY > SALINITY

Cruise Report

http://www.godac.jamstec.go.jp/catalog/data/doc_catalog/media/MR10-01_leg1-2_all.pdf

i For Using Data

Principal Investigator

Data Management Office

Use Constraints

See [Terms and Conditions](#) about constrain of use.

Data Citation

See [Terms and Conditions](#) about data citation.

Instrument


Instrument:

Water sampling system with CTD (30
litters * 24 bottles)




Instrument:

Water sampling system with CTD (12
litters * 36 bottles)




Instrument:

Water sampling system with CTD (12
litters * 12 bottles)



Instrument:

Conductivity temperature depth
measurements (CTD)



Overview

CTD(Conductivity-Temperature-Depth profiler) is used to observe the vertical profiles of temperature and conductivity.

Usually, this system is operated with multicylinder water sampler.

Observed signal is transmitted from sensor to the operation room on board using wire cable, and electric power is supplied from vessel to sensor.

Details of sensors attached to CTD system for MR10-01 Leg1 cruise are presented in "System".

The following software, developed and supplied by the Sea-Bird Electronics, Inc., was used in MR10-01 Leg1.

SEASAVE(ver 7.19) for data acquisition

SEASOFT(ver 7.18d) for data processing

Data presented on this website is averaged over 1db.

System

• Pressure sensor

Model : SBE9plus, Sea-Bird Electronics,Inc.

Serial number : 79492

Measurement range : up to 10500m

Accuracy : 0.015% F.S.

Resolution : 0.001% F.S.

• Temperature sensor

Model : SBE3, Sea-Bird Electronics,Inc.

Serial number : 031464

Measurement range : -5.0 to +35degC

Accuracy : 0.001degC

Resolution : 0.0002degC

• Temperature sensor

Model : SBE3, Sea-Bird Electronics,Inc.

Serial number : 032453

Measurement range : -5.0 to +35degC

Accuracy : 0.001degC

- Resolution : 0.0002degC
- Salinity sensor
 - Model : SBE4, Sea-Bird Electronics, Inc.
 - Serial number : 041172
 - Measurement range : 0.0 to 7 S/m
 - Accuracy : 0.0003 S/m
 - Resolution : 0.00004 S/m
 - DO sensor
 - Model : SBE43, Sea-Bird Electronics, Inc.
 - Serial number : 430330
 - Measurement range : 120% of surface saturation
 - Accuracy : 2% of saturation

Sensors used in each cast is as follows.

Cast name	Serial number of sensor			Dissolved Oxygen
	Pressure	Temperature	Salinity	
JKOM01	79492	031464	041172	430330
KNTM01	79492	032453	041172	430330
K02M01	79492	032453	041172	430330
K02M02	79492	032453	041172	430330
K02M03	79492	032453	041172	430330
K02M04	79492	032453	041172	430330
K02M05	79492	032453	041172	430330
S01M01	79492	032453	041172	430330
S01M02	79492	032453	041172	430330
S01M03	79492	032453	041172	430330
S01M04	79492	032453	041172	430330
S01M05	79492	032453	041172	430330
S01M06	79492	032453	041172	430330
S01M07	79492	032453	041172	430330
S01M08	79492	032453	041172	430330

Calibration Information

Calibration Information is as follows.

[Calibration Information](#)

Data processing

(1) Data processing sequence for SEASOFT is as follows;

(* is not SEASOFT original procedure.)

command	function
datcrv	Convert raw data to engineering units, and store converted data in file.
tcorp*	Corrected the pressure sensitivity of the temperature(SBE3) sensor.
alignctd	Align data relative to pressure(typically used for conductivity, temperature, and oxygen).
wildedit	Mark a data value with badflag to eliminate wild points.
celltm	Perform conductivity thermal mass correction.
filter	Low-pass filter columns of data.
wfilter	Median filter removes spikes of fluorometer data.
section	Extract rows of data from file.
loopedit	Mark a scan with badflag if scan fails pressure reversal or minimum velocity tests.
despike*	Remove spikes of the data.
derive	Calculate oxygen. (with oxygen sensor)
binavg	Average data, basing bins on pressure, depth, scan number, or time range.
derive	Calculate salinity, density, etc..
split	Split data in file into upcast and downcast files.

(2) Quality control

QCed data were added flag according to the NODC (National Oceanographic Data Center) quality control procedure.

- 1) The gradient check of adjacent depth data
- 2) The density inversion check
- 3) The broad range check set up at given ocean space and depth

Please see the site of NODC of the following link for quality control procedure in detail.

[QUALITY CONTROL AND PROCESSING OF HISTORICAL OCEANOGRAPHIC TEMPERATURE, SALINITY, AND OXYGEN DATA](#)

In addition, an abnormal value is identified by a visual check, and the data after visual QC is released.

Note

(1) In this cruise, there is extra data (fluorescence intensity, transmittance, distance to bottom) in additional to temperature, salinity, dissolved oxygen that has been opened to the public. Please contact us from "Contact Us" above if necessary.

Related Information

MR10-01 Leg1


Ship Name: MIRAI

Period: 2010-01-19 - 2010-02-06

Chief Scientist: Kazuhiko Matsumoto (JAMSTEC)

Project Name: [Station K2, Station S1, Station KEO, Station KNOT]

Proposal ▶ Change in material cycles and ecosystem by the climate change and its feed back
Title:



Update History

2017-06-22	An observation data was registerd.
2014-08-06	An observation data was registerd.
2014-02-15	An observation data was registerd.
2014-02-13	An observation data was registerd.
2013-03-27	An observation data was registerd.
2012-09-28	An observation data was registerd.

JAMSTEC

Site Policy
Privacy Policy
Application for Data and Samples
Data Policy
What's New
Update History
Feeds

Lists

Publication List
Amount of Public Info.
Data
Map Search
Data Tree
Detailed Search

Information of the Ships

NATSUSHIMA
KAIYO
YOKOSUKA
MIRAI
KAIREI
CHIKYU
KAIMEI
SHINSEI MARU
HAKUHO MARU

Information of the Submersibles

KAIKO
SHINKAI 2000
SHINKAI 6500
DEEP TOW
HYPER-DOLPHIN
URASHIMA
YOKOSUKA DEEP TOW
6K Camera DEEP TOW
6K Sonar DEEP TOW
KM-ROV
POWER GRAB SAMPLER (SHELL)
POWER GRAB SAMPLER (CLOW)
BMS

Go to a Cruise Information

Cruise ID:

Go to a Dive Information

Dive ID:



MIRAI MR10-01 Leg1 Conductivity-Temperature-Depth Profiler (CTD)

Last Modified: 2017-06-22

[ReadMe](#) [Observation Data](#) [Data Format](#)

Cruise ID: [MR10-01 Leg1](#)

Conductivity-Temperature-Depth Profiler (CTD): Processed (DMO)-QCed

Data Policy: [JAMSTEC](#)

CTD DMO

Format Description for the Corrected Data

Provided in the Exchange Format of CCHDO (CLIVAR and Carbon Hydrographic Data Office). Please see the following link for details of Exchange Format.

[CCHDO | CLIVAR & Carbon Hydrographic Data Office](#)

Data in following cruise is not expressed with Exchange Format. Please see the site of each cruise for format.

MR02-K05 Leg1

MR04-05

Format Description for the QCed Data

Each data file contains one line header (meta data) followed by data lines for each cast.

The number of data lines are recorded in the header.

Header part

No.	Column	Content	Format	Remarks
1	1	Header ID	a1	fixed as '#'
2	3 - 6	Data ID	a4	CTD
3	8 - 22	Cruise ID	a15	MYYY-(K)XX(_legx)
4	24 - 31	Cast name	a8	
5	33 - 40	Date	i8	YYYYMMDD (UTC)
6	42 - 45	Time	i4	hhmm (UTC)
7	47 - 55	Latitude	i2,a1,f5.2,a1	dd-mm.mmN(S)
8	57 - 66	Longitude	i3,a1,f5.2,a1	ddd-mm.mmE(W)
9	68 - 71	Number of data lines	i4	
10	72 - 73	Terminator	-	CR+LF

Data part

No.	Column	Content	Unit	Format	Remarks
1	1 - 11	Pressure	dbar	f11.3	
2	12 - 22	Temperature	deg-C	f11.4	ITS-90
3	23 - 33	Salinity	PSU	f11.4	PSS-78
4	34 - 44	Dissolved oxygen	umol/kg	f11.3	
5	45 - 55	Flag	-	i11	1 - 7 : space 8 : flag of pressure 9 : flag of temperature 10 : flag of salinity 11 : flag of dissolved oxygen * reference : 'Definition of Quality Control Flags'
6	56 - 57	Terminator	-	-	CR+LF

Each contents of the data part is stored in 11 bytes.

Missing value is presented by '-5', and error value is presented by '-9'.

Definition of Quality Control Flags

1. Depth Flags

- 0 - accepted value
- 1 - error in recorded depth (same or less than previous depth)
- 2 - density inversion

2. Observed Level Flags

- N - missing value
- 0 - accepted value
- 1 - range outlier (outside of broad range check)
- 2 - failed inversion check
- 3 - failed gradient check
- 4 - zero anomaly
- 5 - failed combined gradient and inversion checks
- 6 - failed range and inversion checks
- 7 - failed range and gradient checks
- 8 - failed range and zero anomaly checks
- 9 - failed range and combined gradient and inversion checks
- A - failed visual check

QCed data were added flag according to the NODC (National Oceanographic Data Center) quality control procedure, additionally visually checked. Please see the site of NODC of the following link for quality control procedure.

[QUALITY CONTROL AND PROCESSING OF HISTORICAL OCEANOGRAPHIC TEMPERATURE, SALINITY, AND OXYGEN DATA](#)

Sample Program

[ex_read2.f](#)

Related Information

MR10-01 Leg1


Ship Name: MIRAI

Period: 2010-01-19 - 2010-02-06

Chief Scientist: Kazuhiko Matsumoto (JAMSTEC)

Project Name: [Station K2, Station S1, Station KEO, Station KNOT]

Proposal ▶ Change in material cycles and ecosystem by the climate change and its feed back
Title:



Update History

2017-06-22	An observation data was registerd.
2014-08-06	An observation data was registerd.
2014-02-15	An observation data was registerd.
2014-02-13	An observation data was registerd.
2013-03-27	An observation data was registerd.
2012-09-28	An observation data was registerd.

JAMSTEC

[Site Policy](#)
[Privacy Policy](#)
[Application for Data and Samples](#)
[Data Policy](#)

[What's New](#)
[Update History](#)
[Feeds](#)

Lists

[Publication List](#)
[Amount of Public Info.](#)

[Data](#)
[Map Search](#)
[Data Tree](#)
[Detailed Search](#)

Information of the Ships

NATSUSHIMA
KAIYO
YOKOSUKA
MIRAI
KAIREI
CHIKYU
KAIMEI
SHINSEI MARU
HAKUHO MARU

Information of the Submersibles

KAIKO
SHINKAI 2000
SHINKAI 6500
DEEP TOW
HYPER-DOLPHIN
URASHIMA
YOKOSUKA DEEP TOW
6K Camera DEEP TOW
6K Sonar DEEP TOW
KM-ROV
POWER GRAB SAMPLER (SHELL)
POWER GRAB SAMPLER (CLOW)
BMS

Go to a Cruise Information

Cruise ID:

Go to a Dive Information

Dive ID:



MIRAI MR10-01 Leg1 Conductivity-Temperature-Depth Profiler (CTD)

Last Modified: 2017-06-22

[ReadMe](#) [Observation Data](#) [Data Format](#)

Cruise ID: [MR10-01 Leg1](#)

Conductivity-Temperature-Depth Profiler (CTD): Processed (DMO)-QCed

Data Policy: [JAMSTEC](#)


Observation Items: Pressure, Temperature, Salinity, Dissolved oxygen

Science Keywords:

- OCEANS > OCEAN CHEMISTRY > OXYGEN
- OCEANS > OCEAN > WATER
- TEMPERATURE TEMPERATURE
- OCEANS > SALINITY/DENSITY > SALINITY

Observation Map

- Clicking the icon displays a balloon with observation information.
- Then click the observation name, figures will be displayed.



— ... Observation Line — ... Navigation ● ... Observation, Dive Point, Hole


Imagery reproduced from ...

Figures

JKOM01



MR10-01 Leg1:JKOM01
Conductivity-Temperature-Depth Profiler (CTD):Salinity



Only values evaluated as "good : all flags are 0" are plotted in profiles.
Please see Format Page for the definition of quality flags.

Data List

[Add to Basket](#)


<input type="checkbox"/> File names
<input type="checkbox"/> JKOM01.dat
<input type="checkbox"/> K02M01.dat
<input type="checkbox"/> K02M02.dat
<input type="checkbox"/> K02M03.dat
<input type="checkbox"/> K02M04.dat
<input type="checkbox"/> K02M05.dat
<input type="checkbox"/> KNTM01.dat
<input type="checkbox"/> S01M01.dat
<input type="checkbox"/> S01M02.dat
<input type="checkbox"/> S01M03.dat
<input type="checkbox"/> S01M04.dat
<input type="checkbox"/> S01M05.dat
<input type="checkbox"/> S01M06.dat

- File Manager
- S01M08.dat
- ex_read2.f (Sample Program)

● Observation List
The list of observation is shown as follows.

Observation	Time and Date	Lat. [°]	Lon. [°]
JKOM01	2010-01-21 01:20	38.0630	146.5096
K02M01	2010-01-24 07:54	46.9983	159.9763
K02M02	2010-01-24 18:54	47.0041	159.9698
K02M03	2010-01-25 07:07	46.8573	160.0731
K02M04	2010-01-25 18:53	46.9531	160.2126
K02M05	2010-01-25 22:05	47.0141	160.2655
KNTM01	2010-01-22 22:54	43.9993	154.9951
S01M01	2010-01-30 22:25	29.9365	144.9683
S01M02	2010-01-30 23:07	29.9366	144.9660
S01M03	2010-01-31 05:54	30.0633	144.9663
S01M04	2010-01-31 18:56	29.9985	145.0000
S01M05	2010-02-01 05:43	29.9303	144.9833
S01M06	2010-02-01 07:22	29.8960	145.0095
S01M07	2010-02-02 05:52	30.0615	144.9373
S01M08	2010-02-02 18:55	30.0085	145.4300

Related Information



[Enlarge Image](#)

MR10-01 Leg1

Ship Name: MIRAI
 Period: 2010-01-19 - 2010-02-06
 Chief Scientist: Kazuhiko Matsumoto (JAMSTEC)
 Project Name: [Station K2, Station S1, Station KEO, Station KNOT]
 Proposal ▶ Change in material cycles and ecosystem by the climate change and its feed back
 Title:

Update History

2017-06-22	An observation data was registered.
2014-08-06	An observation data was registered.
2014-02-15	An observation data was registered.
2014-02-13	An observation data was registered.
2013-03-27	An observation data was registered.
2012-09-28	An observation data was registered.

JAMSTEC

Site Policy
 Privacy Policy
 Application for Data and Samples
 Data Policy
 What's New
 Update History
 Feeds

Lists

Publication List
 Amount of Public Info.
 Data
 Map Search
 Data Tree
 Detailed Search

Information of the Ships

NATSUSHIMA
 KAIYO
 YOKOSUKA
 MIRAI
 KAIREI
 CHIKYU
 KAIMEI
 SHINSEI MARU
 HAKUHO MARU

Information of the Submersibles

KAIKO
 SHINKAI 2000
 SHINKAI 6500
 DEEP TOW
 HYPER-DOLPHIN
 URASHIMA
 YOKOSUKA DEEP TOW
 6K Camera DEEP TOW
 6K Sonar DEEP TOW
 KM-ROV
 POWER GRAB SAMPLER (SHELL)
 POWER GRAB SAMPLER (CLOW)
 BMS

Go to a Cruise Information

Cruise ID:

Go to a Dive Information

Dive ID:

