

URASHIMA URSM 00139 Submersible Conductivity-Temperature-Depth Profiler (CTD)

Last Modified: 2021-09-04

ReadMe Observation Data Data Format

Dive No.: [URSM 00139](#)

Submersible Conductivity-Temperature-Depth Profiler (CTD): Processed (DMO)-QCed

Data Policy: [JAMSTEC](#)

Observation Items: Depth/Pressure, Temperature, Salinity

Science Keywords:

OCEANS > OCEAN > WATER
TEMPERATURE TEMPERATURE
OCEANS > SALINITY/DENSITY > SALINITY

Cruise Report

http://www.godac.jamstec.go.jp/catalog/data/doc_catalog/media/YK11-10_all.pdf

For Using Data

Principal Investigator

Data Management Office

Use Constraints

See [Terms and Conditions](#) about constrain of use.

Data Citation

See [Terms and Conditions](#) about data citation.


Instrument

Instrument:

CTD measurement system equipped on

the autonomous underwater vehicle

"URASHIMA"



Overview

The CTD system mounted on the deep-sea cruising vehicle "URASHIMA" is consisted of SBE-49 FastCAT CTD Sensor of Sea-Bird Electronics, Inc. The primary detection element is installed vertically on the front center part of the vehicle. Its withstand depth is 7000m and its maximum depth of use is 3500m. Each parameter of conductivity, water temperature, and pressure can be measured in 1Hz and is transmitted to the CTD processing part. In the processing part, ASCII conversion is conducted.

Specifications

SBE-49 FastCAT, Sea-Bird Electronics, Inc.

Sensor	Measurement range	Accuracy	Model
Temperature	-5 to +35 deg-C	0.002 deg-C	SBE 49
Conductivity	0 to 9 S/m	0.0003 S/m	
Pressure	0 to 10000 psia	0.1% of full scale range	

Data collection and situations

The data collection in each dive starts from the moment of operation confirmation on deck and ends immediately after it comes up to the sea surface.

The primary detecting element is installed on about the same height of the pressure gauge.

The seawater intake mouth projects from a crust in a plastic tube to lower influence of the disorder of the seawater with the vehicle.

The internal clock of CTD is synchronized, in each dive, with "URASHIMA" NTP server.

Data available here

The data available on this web site is 1-sec mean CTD data integrated with "URASHIMA" (hereafter, the submersible vehicle) positioning data in latitude and longitude.

The SSBL (Super Short Base Line) method is used to measure the submersible vehicle's position, which requires transponder mounted on the submersible vehicle and an array of transducers equipped on the bottom of the mother ship. The position is measured by both phase lag measured from angles of received sound waves and distance calculated from travelling period of them. Because the baseline length (i.e., a distance between transducers and the transponder) is short, a horizontal error is about 2.5% of slant range (i.e., a distance between the submersible vehicle and the mother ship). The SSBL method has a characteristic that it is a little less accurate but easier to operate than the LBL (Long Base Line) method because it doesn't need to deploy sea-bed mounted transponder(s). Vertical profile of sound velocity is needed to calculate accurate distance from the travelling period. Therefore, the temperature measurement using XBT etc. of each sea area is executed.

The submersible vehicle positioning data was calculated by adding the relative distance to the mother ship's position. The simplified equation with the area-dependent coefficients every 30 degrees in latitude and longitude was applied to the distance (XY) to Lon/Lat conversion, which provided by Japan Coast Guard. Here, the original time interval of position data is more than 10 seconds. The noises remaining in the position data are manually eliminated and linearly interpolated when the speed calculated from adjacent two position data is greater than 4 knot which is the maximum operation speed of the submersible vehicle. Moreover, noises remained in the depth, temperature, and salinity data are visually checked and replaced to missing values only when the data seemed to be obviously abnormal.


The CTD system was installed as one of the navigation equipment to monitor the ambient environmental conditions of the submersible vehicle, of which sensor calibration is normally executed about every two years.

After considering the accuracy of the sensors, the significant digit of data was changed as in the following list.

Data	Raw	On this web site
Pressure	0.001 [dbar]	0.1 [dbar]
Temperature	0.0001 [deg-C]	0.01 [deg-C]
Salinity	0.0001 [PSU]	0.01 [PSU]

Related Information

[Cruise Data](#) [Dive Data](#)



YK11-10

Ship Name: YOKOSUKA

Period: 2011-11-15 - 2011-12-06

Chief Scientist: Tamaki Ura (The University of Tokyo)

Proposal Title: Development of Strategy for Finding and Observing Hydro-Thermal Vent Fields in West Part of Okinawa Trough such as No. 4 Yonaguni Knolls by Using Two Autonomous Underwater Vehicles

Update History

2021-09-04	An observation data was registerd.
2018-09-30	An observation data was registerd.

JAMSTEC

Site Policy

Privacy Policy

Application for Data and Samples

Data Policy

What's New

Update History

Feeds

Lists

Publication List

Amount of Public Info.

Data

Map Search

Data Tree

Detailed Search

Information of the Ships

NATSUSHIMA

KAIYO

YOKOSUKA

MIRAI

KAIREI

CHIKYU

KAIMEI

SHINSEI MARU

HAKUHO MARU

Information of the Submersibles

KAIKO

SHINKAI 2000

SHINKAI 6500

DEEP TOW

HYPER-DOLPHIN

URASHIMA

YOKOSUKA DEEP TOW

6K Camera DEEP TOW

6K Sonar DEEP TOW

KM-ROV

POWER GRAB

SAMPLER (SHELL)

POWER GRAB

SAMPLER (CLOW)

BMS

Go to a Cruise Information

Cruise ID:

Go to a Dive Information

Dive ID:

Copyright 2011 Japan Agency for Marine-Earth Science and Technology



JAMSTEC

国立研究開発法人
海洋研究開発機構
JAPAN AGENCY FOR MARINE-EARTH SCIENCE AND TECHNOLOGY

URASHIMA URSM 00139 Submersible Conductivity-Temperature-Depth Profiler (CTD)

Last Modified: 2021-09-04

[ReadMe](#) [Observation Data](#) [Data Format](#)

Dive No.: [URSM 00139](#)

Submersible Conductivity-Temperature-Depth Profiler (CTD): Processed (DMO)-QCed

Data Policy: [JAMSTEC](#)

Submersible CTD Qced (URSM)

Header part

No.	Column	Item	Format	Remarks
1	1	Header ID	a1	fixed as '#'
2	3 - 37	Submersible vehicle	a35	URASHIMA
3	39 - 48	Data ID	a10	CTD
4	50 - 70	Cruise ID	a21	YKYY-XX(_legx)
5	78 - 81	Dive number	a4	


Data part

No.	Column	Item	Unit	Format	Remarks
1	1 - 8	Date	-	i8	YYYYMMDD (LST)
2	10 - 15	Time	-	i6	hhmmss (LST)
3	17 - 26	Latitude	degree	f10.5	No sign for the northern hemisphere. Negative for the southern hemisphere.
4	28 - 37	Longitude	degree	f10.5	No sign for the eastern hemisphere. Negative for the western hemisphere.
5	39 - 48	Pressure	dbar	f10.1	
6	50 - 59	Temperature	deg-C	f10.2	ITS-90
7	61 - 70	Salinity	PSU	f10.2	PSS-78
8	72 - 81	Dissolved oxygen	ml/l	f10.1	
9	83 - 92	Altitude	m	f10.1	
10	94 - 103	Roll	degree	f10.1	
11	105 - 114	Pitch	degree	f10.1	
12	116 - 125	Vehicle heading	degree	f10.1	

Missing value is presented by '-999'.

Related Information

☒ Cruise Data ☐ Dive Data



[Enlarge Image](#)

YK11-10

Ship Name: YOKOSUKA

Period: 2011-11-15 - 2011-12-06

Chief Scientist: Tamaki Ura (The University of Tokyo)

Proposal Title: Development of Strategy for Finding and Observing Hydro-Thermal Vent Fields in West Part of Okinawa Trough such as No. 4 Yonaguni Knolls by Using Two Autonomous Underwater Vehicles

Update History

2021-09-04	An observation data was registerd.
2018-09-30	An observation data was registerd.

JAMSTEC

[Site Policy](#)

[Privacy Policy](#)

[Application for Data and Samples](#)

[Data Policy](#)

[What's New](#)

[Update History](#)

[Feeds](#)

Lists

[Publication List](#)

[Amount of Public Info.](#)

Data

[Map Search](#)

[Data Tree](#)

[Detailed Search](#)

Information of the Ships

[NATSUSHIMA](#)

[KAIYO](#)

[YOKOSUKA](#)

[MIRAI](#)

[KAIREI](#)

[CHIKYU](#)

[KAIMEI](#)

[SHINSEI MARU](#)

[HAKUHO MARU](#)

Information of the Submersibles

[KAIKO](#)

[SHINKAI 2000](#)

[SHINKAI 6500](#)

[DEEP TOW](#)

[HYPER-DOLPHIN](#)

[URASHIMA](#)

[YOKOSUKA DEEP TOW](#)

[6K Camera DEEP TOW](#)

[6K Sonar DEEP TOW](#)

[KM-ROV](#)

[POWER GRAB SAMPLER \(SHELL\)](#)

[POWER GRAB SAMPLER \(CLOW\)](#)

[BMS](#)

Go to a Cruise Information

Cruise ID:

Go to a Dive Information

Dive ID:

URASHIMA URSM 00139 Submersible Conductivity-Temperature-Depth Profiler (CTD)

Last Modified: 2021-09-04

[ReadMe](#) [Observation Data](#) [Data Format](#)

Dive No.: **URSM 00139**

Submersible Conductivity-Temperature-Depth Profiler (CTD): Processed (DMO)-QCed


Data Policy: **JAMSTEC**

Observation Items: Depth/Pressure, Temperature, Salinity


Science Keywords:

OCEANS > OCEAN > WATER
OCEANS > TEMPERATURE > TEMPERATURE
OCEANS > SALINITY/DENSITY > SALINITY

Observation Map



Figures



Data List


[Add to Basket](#)

File names

☐ URSM_00139.txt

Related Information

[Cruise Data](#) [Dive Data](#)



YK11-10

Ship Name: YOKOSUKA

Period: 2011-11-15 - 2011-12-06

Chief Scientist: Tamaki Ura (The University of Tokyo)

Proposal: Development of Strategy for Finding and Observing Hydro-Thermal Vent Fields in West Part of Okinawa Trough such as No. 4 Yonaguni Knolls by Using Two Autonomous Underwater Vehicles

[Enlarge Image](#)

Update History

2021-09-04 An observation data was registered.
2018-09-30 An observation data was registered.

[Privacy Policy](#)
[Application for Data and Samples](#)
[Data Policy](#)
What's New
[Update History](#)
[Feeds](#)

[Amount of Public Info.](#)
Data
[Map Search](#)
[Data Tree](#)
[Detailed Search](#)

[KAIYO](#)
[YOKOSUKA](#)
[MIRAI](#)
[KAIREI](#)
[CHIKYU](#)
[KAIMEI](#)
[SHINSEI MARU](#)
[HAKUHO MARU](#)

[KAIKO](#)
[SHINKAI 2000](#)
[SHINKAI 6500](#)
[DEEP TOW](#)
[HYPER-DOLPHIN](#)
[URASHIMA](#)
[YOKOSUKA DEEP TOW](#)
[6K Camera DEEP TOW](#)
[6K Sonar DEEP TOW](#)
[KM-ROV](#)
[POWER GRAB SAMPLER \(SHELL\)](#)
[POWER GRAB SAMPLER \(CLOW\)](#)
[BMS](#)

Cruise ID:

[Go to a Dive Information](#)

Dive ID: