

KAIKO KAIKO 00649 Submersible Conductivity-Temperature-Depth Profiler (CTD)

Last Modified: 2021-02-19

Dive No.: **KAIKO 00649**

Submersible Conductivity-Temperature-Depth Profiler (CTD): Processed (DMO)-QCed

Data Policy: **JAMSTEC**

Observation Items: Depth/Pressure, Temperature, Salinity, Dissolved oxygen

Science Keywords:

OCEANS > OCEAN CHEMISTRY > OXYGEN
 OCEANS > OCEAN > WATER
 OCEANS TEMPERATURE TEMPERATURE
 OCEANS > SALINITY/DENSITY > SALINITY

Cruise Report

http://www.godac.jamstec.go.jp/catalog/data/doc_catalog/media/KR15-03_all.pdf

For Using Data

Principal Investigator

Data Management Office

Use Constraints

See [Terms and Conditions](#) about constrain of use.


Data Citation

See [Terms and Conditions](#) about data citation.

Instrument

Instrument:

CTD/DO measurement system
equipped on the remotely operated
vehicle "KAIKO"



Overview

The CTD system mounted on the remotely operated vehicle "KAIKO" is consisted of SBE-49 FastCAT CTD Sensor of Sea-Bird Electronics, Inc. and RINKO II DO Sensor of JFE Advantech Co., Ltd. Its withstand depth is 10500m and its maximum depth of use is 7000m. Each parameter of conductivity, water temperature, and pressure, and dissolved oxygen (DO) can be measured in 1Hz and is transmitted to the CTD processing part. In the processing part, ASCII conversion is conducted.

Specifications

SBE-49 FastCAT, Sea-Bird Electronics, Inc. & RINKO II DO Sensor of JFE Advantech Co., Ltd.

Sensor	Measurement range	Accuracy	Model
Temperature	-5 to +35 deg-C	0.002 deg-C	SBE 49
Conductivity	0 to 9 S/m	0.0003 S/m	
Pressure	0 to 15000 psia	0.1% of full scale range	
Dissolved oxygen	0 to 15 ml/l	0.1 ml/l	RINKO II

Data collection and situations

A data collection period in each dive is from the depth 30-50m when submerging, until the depth 10-20m when floating.

Because of the installed position of the primary detecting element, actual observation depth of CTD will be approximately 1m higher than the depth of the sea bottom.

The internal clock of CTD is synchronized, in each action, with ship's time server.

Data available here

The data available on this web site is 1-sec mean CTD data integrated with "KAIKO" vehicle (hereafter, the submersible vehicle) positioning data in latitude and longitude. The SSBL (Super Short Base Line) method is used to measure the submersible vehicle's position, which requires transponder mounted on the rear part of the vehicle and an array of transducers equipped on the lower front of the launcher. The position is measured by both phase lag measured from angles of received sound waves and distance calculated from travelling period of them. Because the baseline length (i.e., a distance between transducers and the transponder) is short, a horizontal error is about 2.5% of slant range (i.e., a distance between the submersible vehicle and the mother ship). The SSBL method has a characteristic that it is a little less accurate but easier to operate than the LBL (Long Base Line) method because it doesn't need to deploy sea-bed mounted transponder(s). Vertical profile of sound velocity is needed to calculate accurate distance from the travelling period. Therefore, the temperature measurement using XBT etc. of each sea area is executed.

The submersible vehicle positioning data was calculated by adding the relative distance to the mother ship's position. The simplified equation with the area-dependent coefficients every 30 degrees in latitude and longitude was applied to the distance (XY) to Lon/Lat conversion, which provided by Japan Coast Guard. Here, the original time interval of position data is more than 10 seconds. The noises remaining in the position data are manually eliminated and linearly interpolated when the speed calculated from adjacent two position data is greater than 1.5 knot which is the maximum operation speed of the submersible vehicle. Moreover, noises remained in the depth, temperature, and salinity data are visually checked and replaced to missing values only when the data seemed to be obviously abnormal.

The CTD/DO system was not installed as the observation equipment, but installed as one of the navigation equipment to monitor the ambient environmental conditions of the vehicle. So, note that the calibration interval of the equipment is not especially provided and the calibration of the equipment is irregularly executed.

After considering the accuracy of the sensors, the significant digit of data was changed as in the following list.

Data	Raw	On this web site
Pressure	0.001 [dbar]	0.1 [dbar]
Temperature	0.01 [deg-C]	0.01 [deg-C]
Salinity	0.001 [PSU]	0.01 [PSU]
Dissolved oxygen	0.001 [ml/l]	0.1 [ml/l]

Related Information



Ship Name: KAIREI
Period: 2015-02-19 - 2015-03-01
Chief Scientist: Hiroaki Toh (Kyoto University)
Proposal Title: Monitoring of tsunamis by long-term seafloor EM observation

Update History

2021-02-19	An observation data was registerd.
2018-03-30	An observation data was registerd.

JAMSTEC
Site Policy
Privacy Policy
Application for Data and Samples
Data Policy
What's New
Update History
Feeds

- Lists
 - Publication List
 - Amount of Public Info.

- Data
- Map Search
- Data Tree
- Detailed Search

Information of the Ships

NATSUSHIMA
KAIYO
YOKOSUKA
MIRAI
KAIREI
CHIKYU
KAIMEI
SHINSEI MARU
HAKUHO MARU

Information of the Submersibles

KAIKO
SHINKAI 2000
SHINKAI 6500
DEEP TOW
HYPER-DOLPHIN
URASHIMA
YOKOSUKA DEEP TOW
6K Camera DEEP TOW
6K Sonar DEEP TOW
KM-ROV
POWER GRAB
SAMPLER (SHELL)
POWER GRAB
SAMPLER (CLOW)
BMS

Go to a Cruise Information

Cruise ID: Go

Go to a Dive Information

Dive ID:

Copyright 2011 Japan Agency for Marine-Earth Science and Technology



JAMSTEC

国立研究開発法人
海洋研究開発機構

KAIKO KAIKO 00649 Submersible Conductivity-Temperature-Depth Profiler (CTD)

Last Modified: 2021-02-19

[ReadMe](#) [Observation Data](#) [Data Format](#)

Dive No.: **KAIKO 00649**

Submersible Conductivity-Temperature-Depth Profiler (CTD): Processed (DMO)-QCed

Data Policy: [JAMSTEC](#)

Submersible CTD Qced (KAIKO)

Header part

No.	Column	Item	Format	Remarks
1	1	Header ID	a1	fixed as '#'
2	3 - 37	Submersible vehicle	a35	KAIKO
3	39 - 48	Data ID	a10	CTD
4	50 - 70	Cruise ID	a21	KRYY-XX(_legx)
5	78 - 81	Dive number	a4	


Data part

No.	Column	Item	Unit	Format	Remarks
1	1 - 8	Date	-	i8	YYYYMMDD (LST)
2	10 - 15	Time	-	i6	hhmmss (LST)
3	17 - 26	Latitude	degree	f10.5	No sign for the northern hemisphere. Negative for the southern hemisphere.
4	28 - 37	Longitude	degree	f10.5	No sign for the eastern hemisphere. Negative for the western hemisphere.
5	39 - 48	Pressure	dbar	f10.1	
6	50 - 59	Temperature	deg-C	f10.2	ITS-90
7	61 - 70	Salinity	PSU	f10.2	PSS-78
8	72 - 81	Dissolved oxygen	ml/l	f10.1	
9	83 - 92	Altitude	m	f10.1	
10	94 - 103	Vehicle heading	degree	f10.1	
11	105 - 114	pan	degree	f10.1	
12	116 - 125	tilt	degree	f10.1	

Missing value is presented by '-999'.

Related Information

☒ Cruise Data ☐ Dive Data



[Enlarge Image](#)

KR15-03

Ship Name: KAIKEI

Period: 2015-02-19 - 2015-03-01

Chief Scientist: Hiroaki Toh (Kyoto University)

Proposal: Monitoring of tsunamis by long-term seafloor EM observation

Title:

Update History

2021-02-19	An observation data was registered.
2018-03-30	An observation data was registered.

JAMSTEC

[Site Policy](#)

[Privacy Policy](#)

[Application for Data and Samples](#)

[Data Policy](#)

[What's New](#)

[Update History](#)

[Feeds](#)

Lists

[Publication List](#)

[Amount of Public Info.](#)

Data

[Map Search](#)

[Data Tree](#)

[Detailed Search](#)

Information of the Ships

[NATSUSHIMA](#)

[KAIYO](#)

[YOKOSUKA](#)

[MIRAI](#)

[KAIREI](#)

[CHIKYU](#)

[KAIMEI](#)

[SHINSEI MARU](#)

[HAKUHO MARU](#)

Information of the Submersibles

[KAIKO](#)

[SHINKAI 2000](#)

[SHINKAI 6500](#)

[DEEP TOW](#)

[HYPER-DOLPHIN](#)

[URASHIMA](#)

[YOKOSUKA DEEP TOW](#)

[6K Camera DEEP TOW](#)

[6K Sonar DEEP TOW](#)

[KM-ROV](#)

[POWER GRAB SAMPLER \(SHELL\)](#)

[POWER GRAB SAMPLER \(CLOW\)](#)

[BMS](#)

Go to a Cruise Information

Cruise ID:

Go to a Dive Information

Dive ID:

KAIKO KAIKO 00649 Submersible Conductivity-Temperature-Depth Profiler (CTD)

Last Modified: 2021-02-19

[ReadMe](#) [Observation Data](#) [Data Format](#)

Dive No.: **KAIKO 00649**

Submersible Conductivity-Temperature-Depth Profiler (CTD): Processed (DMO)-QCed


Data Policy: **JAMSTEC**

Observation Items: Depth/Pressure, Temperature, Salinity, Dissolved oxygen

Science Keywords:


OCEANS > OCEAN CHEMISTRY > OXYGEN
OCEANS > OCEAN > WATER
TEMPERATURE TEMPERATURE
OCEANS > SALINITY/DENSITY > SALINITY

Observation Map



... Observation Line ... Navigation ... Observation, Dive Point, Hole

Figures



Data List


[Add to Basket](#)

File names

☐ KAIKO_00649.txt

Related Information

[Cruise Data](#) [Dive Data](#)



[Enlarge Image](#)

KR15-03

Ship Name: KAIKEI

Period: 2015-02-19 - 2015-03-01

Chief Scientist: Hiroaki Toh (Kyoto University)

Proposal: Monitoring of tsunamis by long-term seafloor EM observation

Title:

Update History

2021-02-19 An observation data was registerd.
2018-03-30 An observation data was registerd.

JAMSTEC

Site Policy
Privacy Policy

Application for Data and Samples
Data Policy

What's New
Update History
Feeds

Lists

Publication List
Amount of Public Info.

Data

Map Search
Data Tree
Detailed Search

Information of the Ships

NATSUSHIMA
KAIYO
YOKOSUKA
MIRAI
KAIREI
CHIKYU
KAIMEI
SHINSEI MARU
HAKUHO MARU

Information of the Submersibles

KAIKO
SHINKAI 2000
SHINKAI 6500
DEEP TOW
HYPER-DOLPHIN
URASHIMA
YOKOSUKA DEEP TOW
6K Camera DEEP TOW
6K Sonar DEEP TOW
KM-ROV
POWER GRAB SAMPLER (SHELL)
POWER GRAB SAMPLER (CLOW)
BMS

Go to a Cruise Information

Cruise ID:

Go to a Dive Information

Dive ID:

